


Unimat

Heavy-duty anti-fatigue matting for wet areas



- Versatile rubber runner.
- Open holes provide excellent drainage.
- A real asset in helping to prevent slipping in wet areas.
- Easy to roll up and move to new locations or for cleaning.
- Slip tested to DIN 51130.



Parts

Part Number	Size	Colour	Weight (kg)
UM010002C	1 m x per linear metre	Black	
UM010002	1 m x 10 m	Black	74
UM010001	1 m x 5 m	Black	37

Technical Specifications

Material	Rubber mix, including >75% recycled material.
Recycled Material Content %	75%
Surface Finish	Raised anti-slip textured surface with holes to allow drainage
Product Height	10 mm
Product Weight	4 kg
Roll Length	10 m
Min. Operating Temperature	-20°C
Max. Operating Temperature	+130°C
Resistance to Chemicals	Resistant to water and most mild acids

Environmental Resistance	Suitable for wet and dry indoor environments
Typical Applications	General industrial
Installation Method	Loose lay
Cleaning Method	Hose down or pressure wash using a mild detergent
Other Product Performance Information	Impact resistant up to 3 kg /c m ²
COO (Country of Origin)	IN
Tensile Strength	3 to 3.5 MPa
Slip Tested to	DIN 51130 - R10

Additional Information



Unimat - Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com